

# "DOUBLE BOOTH CONQUER"

## SPRAY BOOTH




<b>DIMENSIONS (mm)</b>	<b>EXTERNAL</b>	<b>USEFUL</b>
<b>Length</b>	<b>6800-7460-8120</b>	<b>6600-7260-7920</b>
<b>Width</b>	<b>4080</b>	<b>3960</b>
<b>Height A</b>	<b>3275</b>	<b>2640</b>
<b>Height B-C</b>	<b>3650</b>	<b>2640</b>

## OVEN

<b>DIMENSIONS (mm)</b>	<b>EXTERNAL</b>	<b>USEFUL</b>
<b>Length</b>	<b>6140-6800-7460</b>	<b>5940-6600-7260</b>
<b>Width</b>	<b>3280</b>	<b>3160</b>
<b>Height A</b>	<b>3275 (4030)</b>	<b>2640</b>
<b>Height B-C</b>	<b>3650</b>	<b>2640</b>

## BASEMENTS

<b>A</b>	<b><i>Pit style with gratings</i></b>
<b>B</b>	<b><i>Raised metal basement grating/checkered plates mm 400 (H)</i></b>
<b>C</b>	<b><i>Raised metal basement ramp inside mm 400 (H)</i></b>



### TECHNICAL DATA SPRAY BOOTH

**PLASTIFIED FRONT DOOR** 4 leaves with 4 glasses. Central opening mm 3160x2580(H)  
**SERVICE DOOR**, on front door, right opening (antipanic system)  
**WALLS**, thickness mm 60, in plastified galvanized sheet panels with glass wool material inbetween  
**INSULATED FILTERING PLENUM** wide mm 3200 and having the same length of the spraybooth  
**LIGHTING** fixtures in the upper part with 4 fluorescent tubes of 40 Watt each  
**SIDE ROLL UP DOOR** useful opening mm 6000x2100(H)  
**BURNER** : Oil (Optional: LPG or Natural Gas)  
**HEAT EXCHANGER** in stainless steel  
**EACH SPRAYBOOTH INCLUDES 2,5 m OF GALVANIZED SMOKE CHIMNEY AND CAP**  
**BY-PASS** which opens automatically, recycle of 90% of warm air in cure cycle  
**AUTOMATIC CONTROL PANEL**

### TECHNICAL DATA OVEN

**PLASTIFIED FRONT DOOR** 3 leaves with 3 glasses. Central opening mm 2360x2580(H)  
**WALLS**, thickness 60 mm, in plastified galvanized sheet panels with glass wool material inbetween  
**INSULATED FILTERING PLENUM** wide mm 2400 and having the same length of the spraybooth  
**LIGHTING** fixtures in the upper part with 2 fluorescent tubes of 40 Watt each  
**BURNER** : Oil (Optional: LPG or Natural Gas)  
**HEAT EXCHANGER** in stainless steel  
**EACH SPRAYBOOTH INCLUDES 2,5 m OF GALVANIZED SMOKE CHIMNEY AND CAP**  
**BY-PASS** which opens automatically, recycle of 90% of warm air in cure cycle  
**AUTOMATIC CONTROL PANEL**